

## 48机座封闭式单相电机

# 48 Frame Totally Enclosed Single-Phase Motor

### 性能特点:

- 功率: 1/3HP-1HP
- 极数: 2P, 4P
- 机座: 48
- 卷钢板壳
- 电容启动
- NEMA标准N设计
- 服务系数: 1.0
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: TEFC
- 防护等级: IP44, IP55
- 可接受自动保护器
- 均通过CSA&CUS安全认证

### Features:

- HP: 1/3HP-1HP
- Pole: 2P, 4P
- Frame: 48
- Rolled steel
- Capacitor Start
- NEMA design: N
- Service factor: 1.0
- Insulation Class: F (UL approved)
- Enclosure: TEFC
- IP Class: IP44, IP55
- Accept Auto Thermal Protector
- CSA&CUS certified



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	48	F481/3S2C	115/230	60	TEFC	1.0	3.53/1.8	15
	1800	48	F481/3S4C-1	115/230	60	TEFC	1.0	3.39/1.7	16
1/2	3600	48	F481/2S2C	115/230	60	TEFC	1.0	5.11/2.56	18
	1800	48	F481/2S4C-1	115/230	60	TEFC	1.0	6.92/3.46	21
3/4	3600	48	F483/4S2C	115/230	60	TEFC	1.0	2.93/1.47	20
	1800	48	F483/4S4C	115/230	60	TEFC	1.0	7.37/3.69	22
1	3600	48	F481S2C	115/230	60	TEFC	1.0	9.4/4.7	21
	1800	48	F481S4C	115/230	60	TEFC	1.0	8.91/4.46	25