

56机座4合1电机, 单相

56 Frame Four-in-one Motor, Single-Phase

性能特点:

- 功率: 1/3HP-3HP
- 极数: 2P, 4P
- NEMA标准 L设计
- 卷钢板壳、可拆卸底脚、C法兰
- 电容启动和电容运行
- 服务系数: 1.15
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证
- 可接受手动或自动保护器

Features:

- HP: 1/3HP-3HP
- Pole: 2P, 4P
- NEMA design: L
- Rolled steel frame, Detachable foot, C flange
- Capacitor Start and Capacitor Run
- Service factor: 1.15
- Insulation Class: F(UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified
- Accept Manual or Auto Thermal Protector.



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	% EFF.	WGT. LBS.
1/3	3600	56	F56C 1/3S2C	115/230	60	TEFC	1.15	4.55/2.36	67	23
	1800	56	F56C1/3S4C	115/230	60	TEFC	1.15	4.99/2.58	65	24
1/2	3600	56	F56C1/2S2C	115/230	60	TEFC	1.15	6.01/3.108	68	24
	1800	56	F56C1/2S4C	115/230	60	TEFC	1.15	6.68/3.45	68	25
3/4	3600	56	F56C3/4S2C	115/230	60	TEFC	1.15	8.47/4.29	74	26
	1800	56	F56C3/4S4C	115/230	60	TEFC	1.15	8.27/4.22	74	29
1	3600	56	F56C1S2C	115/230	60	TEFC	1.15	9.44/4.9	77	30
	1800	56	F56C1S4C	115/230	60	TEFC	1.15	9.7/5.04	75	38
1.5	3600	56	F56HC1.5S2C	115/230	60	TEFC	1.15	13.14/6.77	77	37
	1800	56	F56HC1.5S4C	115/230	60	TEFC	1.15	3.63/6.66	77	42
2	3600	56	F56HC2S2C	115/230	60	TEFC	1.15	15.3/7.8	81	44
	1800	56	F56HC2S4C	115/230	60	TEFC	1.15	16.51/8.27	80	47
3	3600	56	F56HC3S2C	115/230	60	TEFC	1.15	24.0/12.3	83	60