

56机座4合1电机, 三相

56 Frame Four-in-one Motor, Three-Phase

性能特点:

- 功率: 1/3HP-3HP
- 极数: 2P, 4P
- NEMA 标准B设计
- 卷钢板壳、可拆卸底脚、C法兰
- 服务系数: 1.15
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过了CSA&CUS安全认证

Features:

- HP: 1/3HP-3HP
- Pole: 2 P, 4 P
- NEMA design: B
- Rolled steel frame, Detachable foot, C flange
- Service factor: 1.15
- Insulation Class: F(UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	F56C 1/3M2A	208-230/460	60	TEFC	1.15	2.3-1.3/0.65	20
	3600	56	F56C 1/3M2D	575	60	TEFC	1.15	0.5	20
	1800	56	F56C 1/3M4A	208-230/460	60	TEFC	1.15	1.71-1.9/0.95	22
	1800	56	F56C 1/3M4D	575	60	TEFC	1.15	0.6	22
	1200	56	F56C 1/3M6A	208-230/460	60	TEFC	1.15	1.64/0.82	22
	1200	56	F56C 1/3M6D	575	60	TEFC	1.15	0.82	23
1/2	3600	56	F56C 1/2M2A	208-230/460	60	TEFC	1.15	2.8-2.0/1.35	23
	3600	56	F56C 1/2M2D	575	60	TEFC	1.15	0.86	23
	1800	56	F56C 1/2M4A	208-230/460	60	TEFC	1.15	3.3-2/1	24.5
	1800	56	F56C 1/2M4D	575	60	TEFC	1.15	1.01	24.5
	1200	56	F56C 1/2M6A	208-230/460	60	TEFC	1.15	2.2/1.1	26
	1200	56	F56C 1/2M6D	575	60	TEFC	1.15	0.93	26.5
3/4	3600	56	F56C 3/4M2A	208-230/460	60	TEFC	1.15	3.3-2.4/1.2	23
	3600	56	F56C 3/4M2D	575	60	TEFC	1.15	0.9	23
	1800	56	F56C3/4M4A	208-230/460	60	TEFC	1.15	4.2-2.8/1.4	28
	1800	56	F56C3/4M4D	575	60	TEFC	1.15	1	28
	1200	56	F56C 3/4M6A	208-230/460	60	TEFC	1.15	2.84/1.42	30
	1200	56	F56C 3/4M6D	575	60	TEFC	1.15	1.31	30
1	3600	56	F56C1M2A	208-230/460	60	TEFC	1.15	3.7-3.2/1.6	24
	3600	56	F56C1M2D	575	60	TEFC	1.15	1.32	24
	1800	56	F56C 1M4A	208-230/460	60	TEFC	1.15	5.4-3.4/1.7	33
	1800	56	F56C 1M4D	575	60	TEFC	1.15	1.6	33
	1200	56	F56C 1M6A	208-230/460	60	TEFC	1.15	2.27/2.41	34
	1200	56	F56C 1M6D	575	60	TEFC	1.15	1.75	34
1.5	3600	56	F56HC1.5M2A	208-230/460	60	TEFC	1.15	5.3-4.2/2.1	29
	3600	56	F56HC1.5M2D	575	60	TEFC	1.15	1.78	29
	1800	56	F56HC1.5M4A	208-230/460	60	TEFC	1.15	6.4-5/2.5	37
	1800	56	F56HC1.5M4D	575	60	TEFC	1.15	2.1	37
2	3600	56	F56HC2M2A	208-230/460	60	TEFC	1.15	6.6-5.2/2.6	34
	3600	56	F56HC2M2D	575	60	TEFC	1.15	2.1	34
	1800	56	F56HC2M4A	208-230/460	60	TEFC	1.15	8.4-6/3	40
	1800	56	F56HC2M4D	575	60	TEFC	1.15	2.5	40
3	3600	56	F56HC3M2A	208-230/460	60	TEFC	1.15	8.5-8/4	39
	3600	56	F56HC3M2D	575	60	TEFC	1.15	3.2	39
	1800	56	F56HC3M4A	208-230/460V	60	TEFC	1.0	4.5	47
	1800	56	F56HC3M4D	575	60	TEFC	1.0	4.3	47