

封闭式单相电容运行电机

Totally Enclosed Single-Phase Capacitor Run Motor

性能特点:

- 功率:1/3HP-3HP
- 极数: 2P, 4P
- 电容运行
- 机座: 56、140T
- 卷钢板壳, 互换C法兰
- NEMA标准N设计
- 服务系数1.15
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证
- 可接受自动保护器

Features:

- HP: 1/3HP-3HP
- Pole: 2P, 4P
- Capacitor Run
- Frame: 56, 140T
- Rolled steel, C-face Kit
- NEMA design: N
- Service factor:1.15
- Insulation Clas: F(UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified;
- Accept Auto Thermal Protector



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	F56 1/3S2C-Y	115/208-230	60	TEFC	1.15	4.7/2.3-2.5	19
	1800	56	F56 1/3S4C-Y	115/208-230	60	TEFC	1.15	4.3/2.1-2.3	19
1/2	3600	56	F56 1/2S2C-Y	115/208-230	60	TEFC	1.15	5.9/2.9-3.1	20
	1800	56	F56 1/2S4C-Y	115/208-230	60	TEFC	1.15	5.8/2.8-3.0	22
3/4	3600	56	F56 3/4S2C-Y	115/208-230	60	TEFC	1.15	8.1/4.2-4.1	24
	1800	56	F56 3/4S4C-Y	115/208-230	60	TEFC	1.15	8.1/4.0-4.2	27
1	3600	56	F56 1S2C-Y	115/208-230	60	TEFC	1.15	8.3/4.8-4.4	26
	3600	143T	F143T1S2C-Y	115/208-230	60	TEFC	1.15	8.3/4.8-4.4	27
	3600	143T	F143T1S2A-Y	208-230/460	60	TEFC	1.15	4.9-4.6/2.4	26
	1800	56	F56 1S4C-Y	115/208-230	60	TEFC	1.15	9.2/5.0-4.7	38
	1800	143T	F143T1S4C-Y	115/208-230	60	TEFC	1.15	9.2/5.0-4.7	39
	1800	143T	F143T1S4A-Y	208-230/460	60	TEFC	1.15	4.9-4.7/2.5	38
1.5	3600	56	F56 1.5S2C-Y	115/208-230	60	TEFC	1.15	13.1/7.0-6.6	33
	3600	145T	F145T1.5S2C-Y	115/208-230	60	TEFC	1.15	13.1/7.0-6.6	34
	3600	145T	F145T1.5S2A-Y	208-230/460	60	TEFC	1.15	7.1-6.3/3.3	33
	1800	56	F56 1.5S4C-Y	115/208-230	60	TEFC	1.15	13.1/7.0-6.6	42
	1800	145T	F145T1.5S4C-Y	115/208-230	60	TEFC	1.15	13.3/7.1-6.6	43
	1800	145T	F145T1.5S4A-Y	208-230/460	60	TEFC	1.15	6.4-5.9/3.0	42
2	3600	56	F56 2S2C-Y	115/208-230	60	TEFC	1.15	16.5/9.1-8.3	43
	3600	145T	F145T2S2C-Y	115/208-230	60	TEFC	1.15	16.5/9.1-8.3	44
	3600	145T	F145T2S2A-Y	208-230/460	60	TEFC	1.15	9.2/8.1-4.1	43
	1800	56	F56 2S4C-Y	115/208-230	60	TEFC	1.15	16.5/9.0-8.3	44
	1800	145T	F145T2S4C-Y	115/208-230	60	TEFC	1.15	16.5/9.0-8.3	43
	1800	145T	F145T2S4A-Y	208-230/460	60	TEFC	1.15	9.4-8.6/4.5	44
3	3600	56	F56 3S2C-Y	115/208-230	60	TEFC	1.15	24.0/13.2-12.3	51
	3600	145T	F145T3S2C-Y	115/208-230	60	TEFC	1.15	24.0/13-12.3	52
	3600	145T	F145T3S2A-Y	208-230/460	60	TEFC	1.15	14-12.5/6.5	51