

感应电动机 INDUCTION MOTOR

60W

□90mm



规格 / 连续额定 SPECS / CONTINUOUS RATING

型号 Model 类型 Type	输出功率 Output power W	电压 Voltage V	频率 Frequency Hz	电流 Current A	启动转矩 Starting Torque mN.m	额定转矩 Rated Torque mN.m	额定转速 Rated Speed r/min	电容器容量 Capacitor μ F
5IK60GN-AF (5IK60A-AF)	60	1ph100	50	1.00	320	470	1250	20.0
5IK60GN-EF (5IK60A-EF)			60	1.10			1550	
5IK60GN-CF (5IK60A-CF)	60	1ph220	50	0.85	300	380	1550	12.0
5IK60GN-HF (5IK60A-HF)			60	0.50			1250	
5IK60GN-SF (5IK60A-SF)	60	1ph230	50	0.55	340	470	1250	4.0
5IK60GN-EFT (5IK60A-EFT)			60	0.50			1550	
5IK60GN-CFT (5IK60A-CFT)	60	1ph220	50	0.55	340	380	1250	-
5IK60GN-HFT (5IK60A-HFT)			60	0.50			1550	
5IK60GN-SFT (5IK60A-SFT)	60	3ph220	50	0.45	1000	470	1250	-
5IK60GN-EFT (5IK60A-EFT)			60	0.40			1550	

● 各种安全规格以电动机铭牌上的型号取得认定。

● When the motor is approved under various safety standards, the model name on the nameplate is the approved model name.

种类 TYPE

● 电动机 MOTOR

机型 Type	型号 Model	
	齿轮轴型 Pinion Shaft	圆轴型 Round Shaft
导线型 Lead Wire Type	5IK60GN-AF	5IK60A-AF
	5IK60GN-EF	5IK60A-EF
	5IK60GN-CF	5IK60A-CF
	5IK60GN-HF	5IK60A-HF
	5IK60GN-SF	5IK60A-SF
带端子箱型 Terminal Box Type	5IK60GN-AFT	5IK60A-AFT
	5IK60GN-EFT	5IK60A-EFT
	5IK60GN-CFT	5IK60A-CFT
	5IK60GN-HFT	5IK60A-HFT
	5IK60GN-SFT	5IK60A-SFT

● 平行轴减速器(另售) PARALLEL SHAFT GEARHEAD (SOLD SEPARATELY)

减速器种类 Gearhead Type	减速器型号 Gearhead Model	减速比 Gear Ratio
长寿命·低噪音 Long Life · Low Noise	5GN□K	3、3.6、5、6、7.5、9、12.5、15、18、25、30、36、50、60、75、90、100、120、150、180、200
	5GN10XK (中间减速器 Mid-gearbox)	

● 减速器型号的□中为减速比的数值

● Enter the gear ratio in the box (□) within the model name

■ 装有减速器时的容许转矩 ALLOWABLE TORQUE WHEN BEING WITH GEARHEAD

- 减速器·中间减速器另售
- 电动机型号的□中为表示带端子箱型的记号 (T)
- 减速器型号的□中为减速比的数值。
- □色表示与电动机同一方向运转，其他则为相反方向。
- 转速是以电动机的同步转速 (50Hz: 1500r/min、60Hz: 1800r/min) 为基准除以减速比而算出来的数值。实际转速将随负载大小变化而比所示数值减少 2%~20%左右。
- 希望以大于下表的减速比进行进一步减速时，可在电动机与减速器之间安装减速比为10的中间减速器。这时的容许转矩为10N·m。
- Gearhead and mid-gearbox can be sold separately.
- Enter the code that represents the terminal box type (T) in the box (□) within the model name.
- Enter the gear ratio in the box (□) within the model name.
- The colored background □ indicates the same rotating direction of the motor while the rotating direction of others are opposite.
- The speed is calculated by dividing the motor's synchronous speed (50Hz: 1500r/min、60Hz: 1800r/min) by the gear ratio. The actual speed is 2%~20% less than the displayed value, depending on the size of the load.
- To reduce the speed beyond the gear ratio in the table, attach a mid-gearbox (gear ratio: 10) between the gearhead and motor. In that case, the permissible torque is 10N·m.

容许力矩单位 Allowance Torque Unit: 上段 Upside (N.m) / 下段 Belowside (kgf.cm)

机型Type 电动机/减速器 Motor/Gearhead	减速比Gear Ratio	容许力矩单位 Allowance Torque Unit: 上段 Upside (N.m) / 下段 Belowside (kgf.cm)																					
		3	3.6	5	6	7.5	9	12.5	15	18	25	30	36	50	60	75	90	100	120	150	180	200	
5IK60GN-AF□ 5IK60GN-EF□ 5IK60GN-CF□ 5IK60GN-HF□ 5IK60GN-SF□	转速Speed r/min	50Hz	500	417	300	250	200	166	120	100	83	60	50	41	30	25	20	16	15	12.5	10	8.3	7.5
	60Hz	600	500	360	300	240	200	144	120	100	72	60	50	36	30	24	20	18	15	12	10	9	9
5GN□K	50Hz	1.1	1.4	1.9	2.3	2.9	3.4	4.8	5.7	6.8	8.6	10	10	10	10	10	10	10	10	10	10	10	10
		11.2	14.2	19.3	23.4	29.6	34.7	48.9	58.1	69.3	87.7	100	100	100	100	100	100	100	100	100	100	100	100
5GN□K	60Hz	0.92	1.1	1.5	1.8	2.3	2.8	3.8	4.6	5.5	6.9	8.3	10	10	10	10	10	10	10	10	10	10	10
		9.38	11.2	15.3	18.3	23.4	28.5	38.7	46.9	56.1	70.1	84.7	100	100	100	100	100	100	100	100	100	100	100

■ 容许悬挂负载·容许轴向负载 PERMISSIBLE OVERHUNG LOAD AND THRUST LOAD

电动机 (圆轴型) → P217 Motor (Round Shaft) → P217
 减速器 → P217 Gearhead → P217

■ 减速器的容许负载惯性惯量 J PERMISSIBLE LOAD INERTIA J FOR GEARHEAD


→ P218页 → P218

■ 外形图 (单位 mm) DIMENSIONS (Unit mm)

减速器附有安装用螺丝
 Mounting screws are included with gearhead.

● 导线型 Lead wiring Type ①

重量 Weight: 电动机 Motor 2.7kg 减速器 Gearhead 1.35kg




电动机型号 Motor Model	减速器型号 Gearhead Model	减速比 Gear Ratio	L1
5IK60GN-AF 5IK60GN-EF 5IK60GN-CF 5IK60GN-HF 5IK60GN-SF	5GN□K	3~18	42
		25~200	60

- 减速器型号的□中为减速比的数值
- Enter the gear ratio in the box (□) within the model name

●带端子箱型Terminal Box Typ②


重量 Weight: 电动机 Motor 2.85kg 减速器 Gearhead 1.35kg



电动机型号 Motor Model	减速器型号 Gearhead Model	减速比 Gear Ratio	L1
5IK60GN-AFT	5GN□K	3~18	42
5IK60GN-EFT			
5IK60GN-CFT			
5IK60GN-HFT	25~200	60	
5IK60GN-SFT			

- 减速器型号的□中为减速比的数值
- Enter the gear ratio in the box (□) within the model name


●键·键槽 (减速器附件) Key-keyway (The key is included with the gearhead)



●圆轴型的转轴部分 Shaft Section of Round Shaft Type

除重量及轴部分, 电动机外形与齿轮轴相同

Excluding weight and the shaft section Motor shape are the same as those of the pinion shaft type




●中间减速器 Mid-gearbox

可安装在GN齿轮轴型上

Can be connected to GN pinion 5GN10XK


重量 Weight: 0.6kg



●电容器外形尺寸 Formal Dimension of Capacitor







型号 Model		电容器型号 Capacitor Model	L	W	H
齿轮轴型 Pinion Shaft	圆轴型 Round Shaft				
5IK60GN-AF□	5IK60A-AF□	ZD200CFAUL	47	23	35
5IK60GN-EF□	5IK60A-EF□	ZD120CFAUL	47	17	31
5IK60GN-CF□	5IK60A-CF□	ZD40BFAUL	47	17	31

- 常规电容器出线为引线, 也可根据客户要求配置插片式187#
- 电动机型号的□中为表示带端子箱型的记号 (T)
- Note: Conventional capacitor is a lead wire type. Inserted 187# is optional
- Enter the code that represents the terminal box type (T) in the box (□) within the model name



连接图 CONNECTION DIAGRAMS

- 运转方向指从电动机轴看来的方向。CW表示顺时针方向，CCW表示逆时针方向。
- 表中所记型号为齿轮轴型，圆轴型亦同。
- The direction of motor rotation is as viewed from the shaft end of motor.
CW represents the clockwise direction, while CCW represents the counterclockwise direction.
- Name indicated in the list is pinion shaft type, also valid for the equivalent round.

导线型 Lead Wire Type		带端子箱型 Terminal Box Type	
5IK60GN-AF、5IK60GN-EF 5IK60GN-CF、5IK60GN-HF	5IK60GN-SF	5IK60GN-AFT、5IK60GN-EFT 5IK60GN-CFT、5IK60GN-HFT	5IK60GN-SFT
<p>顺时针方向 CW</p>  <p>电容器 Capacitance</p>	<p>顺时针方向 CW</p>  <p>电动机 MOTOR</p>	<p>顺时针方向 CW</p>  <p>电动机 MOTOR</p> <p>电容器 Capacitance</p>	<p>顺时针方向 CW</p>  <p>电动机 MOTOR</p>
<p>逆时针方向 CCW</p>  <p>电容器 Capacitance</p>	<p>逆时针方向 CCW</p> <p>若对换R、S、T中任意二条， 电动机作逆时针方向转动 To change the rotation direction change any two connections between R.S and T.</p>	<p>逆时针方向 CCW</p>  <p>电动机 MOTOR</p> <p>电容器 Capacitance</p>	<p>逆时针方向 CCW</p> <p>若对换R、S、T中任意二条， 电动机作逆时针方向转动 To change the rotation direction change any two connections between R.S and T.</p>

● 请注意 Note:

- 单相电动机运转方向的转换应在电动机停止后进行。
- 若在电动机运转时转换运转方向，可能发生无法转换运转方向或须费时较久的情况。
- Change the direction of single-phase motor rotation only after bring the motor to a stop.
- If an attempt is made to change the direction of rotation while the motor is rotating, motor may ignore reversing command or change its direction of rotation after some delay.