

三相JP耦合泵电机

Three-Phase JP Close-Coupled Pump Motor

性能特点:

- 功率: 1HP-10HP
- 极数: 2P, 4P
- 机座: 140T, 180T, 210T
- 卷钢板壳
- NEMA标准B设计
- 电服务系数: 1.15
- 绝缘等级为: F (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证
- 均通过美国EPACT(CC)和加拿大EEV高效认证

Features:

- HP: 1HP-10HP
- Pole: 2P, 4P
- Frame: 140T, 180T, 210T
- Rolled steel
- NEMA design: B
- Service factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified
- EPACT (CC) & EEV certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	3600	143T	F143JP1M2A	208-230/460	60	TEFC	1.15	3.5-3.2/1.6	41
	3600	143T	F143JP1M2D	575	60	TEFC	1.15	1.28	41
	1800	143T	F143JP1M4A	208-230/460	60	TEFC	1.15	3.7-3.4/1.7	56
	1800	143T	F143JP1M4D	575	60	TEFC	1.15	1.36	56
1.5	3600	143T	F143JP1.5M2A	208-230/460	60	TEFC	1.15	4.6-4.2/2.1	51
	3600	143T	143JP1.5M2D	575	60	TEFC	1.15	1.68	51
	1800	145T	F145JP1.5M4A	208-230/460	60	TEFC	1.15	5.5-5.0/2.5	60
	1800	145T	F145JP1.5M4D	575	60	TEFC	1.15	2.0	60
2	3600	145T	F145JP2M2A	208-230/460	60	TEFC	1.15	5.7-5.2/2.6	53
	3600	145T	F145JP2M2D	575	60	TEFC	1.15	2.08	53
	1800	145T	F145JP2M4A	208-230/460	60	TEFC	1.15	6.6-6.0/3.0	63
	1800	145T	F145JP2M4D	575	60	TEFC	1.15	2.24	63
3	3600	182T	F182JP3M2A	208-230/460	60	TEFC	1.15	8.3-7.6/3.8	81
	3600	182T	F182JP3M2D	575	60	TEFC	1.15	3.05	81
	1800	182T	F182JP3M4A	208-230/460	60	TEFC	1.15	8.6-7.8/3.9	100
	1800	182T	F182JP3M4D	575	60	TEFC	1.15	3.2	100
5	3600	184T	F184JP5M2A	208-230/460	60	TEFC	1.15	13.5-12.2/6.1	102
	3600	184T	F184JP5M2D	575	60	TEFC	1.15	4.8	102
	1800	184T	F184JP5M4A	208-230/460	60	TEFC	1.15	14.3-13.0/6.5	106
	1800	184T	F184JP5M4D	575	60	TEFC	1.15	5.28	106
7.5	3600	213T	F213JP.5M2A	208-230/460	60	TEFC	1.15	20.2-18.4/9.2	137
	3600	213T	F213JP7.5M2D	575	60	TEFC	1.15	7.12	137
	1800	213T	F213JP7.5M4A	208-230/460	60	TEFC	1.15	20.7-18.8/9.4	150
	1800	213T	F213JP7.5M4D	575	60	TEFC	1.15	7.35	150
10	3600	215T	F215JP10M2A	208-230/460	60	TEFC	1.15	26.0-23.6/11.8	148
	3600	215T	F215JP10M2D	575	60	TEFC	1.15	9.45	148
	1800	215T	F215JP10M4A	208-230/460	60	TEFC	1.15	27.5-25.0/12.5	157
	1800	215T	F215JP10M4D	575	60	TEFC	1.15	10.0	157

三相JP耦合泵电机

Three-Phase JP Close-Coupled Pump Motor

性能特点:

- 功率: 1HP-15HP
- 极数: 2P, 4P
- 机座: 140T, 180T, 210T
- 卷钢板壳
- NEMA标准B设计
- 服务系数: 1.15
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证
- 均通过美国EPACT(CC)和加拿大EEV高效认证

Features:

- HP: 1HP-15HP
- Pole: 2P, 4P
- Frame: 140T, 180T, 210T
- Rolled steel
- NEMA design: B
- Service factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified
- EPACT (CC) & EEV certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	3600	143T	D143JP1M2A	208-230/460	60	ODP	1.15	3.7-3.4/1.7	35
	3600	143T	D143JP1M2D	575	60	ODP	1.15	1.36	35
	1800	143T	D143JP1M4A	208-230/460	60	ODP	1.15	3.5-3.2/1.6	44
	1800	143T	D143JP1M4D	575	60	ODP	1.15	1.28	44
1.5	3600	143T	D143JP1.5M2A	208-230/460	60	ODP	1.15	4.6-4.2/2.1	41
	3600	143T	D143JP1.5M2D	575	60	ODP	1.15	1.68	41
	1800	145T	D145JP1.5M4A	208-230/460	60	ODP	1.15	5.1-4.6/2.3	47
	1800	145T	D145JP1.5M4D	575	60	ODP	1.15	1.84	47
2	3600	145T	D145JP2M2A	208-230/460	60	ODP	1.15	5.9-5.4/2.7	41
	3600	145T	D145JP2M2D	575	60	ODP	1.15	2.16	41
	1800	145T	D145JP2M4A	208-230/460	60	ODP	1.15	6.8-6.2/3.1	51
	1800	145T	D145JP2M4D	575	60	ODP	1.15	2.48	51
3	3600	145T	D145JP3M2A	208-230/460	60	ODP	1.15	8.8-8.0/4.0	44
	3600	145T	D145JP3M2D	575	60	ODP	1.15	3.2	44
	1800	182T	D182JP3M4A	208-230/460	60	ODP	1.15	8.8-8.0/4.0	84
	1800	182T	D182JP3M4D	575	60	ODP	1.15	3.2	84
5	3600	182T	D182JP5M2A	208-230/460	60	ODP	1.15	14.0-12.8/6.4	79
	3600	182T	D182JP5M2D	575	60	ODP	1.15	5.12	79
	1800	184T	D184JP5M4A	208-230/460	60	ODP	1.15	14.3-13.0/6.5	91
	1800	184T	D184JP5M4D	575	60	ODP	1.15	5.2	91
7.5	3600	184T	D184JP7.5M2A	208-230/460	60	ODP	1.15	20.2-18.4/9.2	86
	3600	184T	D184JP7.5M2D	575	60	ODP	1.15	7.12	86
	1800	213T	D213JP7.5M4A	208-230/460	60	ODP	1.15	20.9-19.0/9.5	133
	1800	213T	D213JP7.5M4D	575	60	ODP	1.15	7.6	133
10	3600	213T	D213JP10M2A	208-230/460	60	ODP	1.15	27.7-25.2/12.6	127
	3600	213T	D213JP10M2D	575	60	ODP	1.15	10.0	127
	1800	215T	D215JP10M4A	208-230/460	60	ODP	1.15	27.5-25.0/12.5	144
	1800	215T	D215JP10M4D	575	60	ODP	1.15	10.0	144
15	3600	215T	D215JP15M2A	208-230/460	60	ODP	1.15	39.8-36.2/18.1	139
	3600	215T	D215JP15M2D	575	60	ODP	1.15	13.8	139