

56机座封闭式三相喷射泵电机

56 Frame Totally Enclosed Three-Phase Jet Pump Motor

性能特点:

- 功率: 1/3HP-3HP
- 极数: 2P
- 机座: 56J
- 卷钢板壳
- NEMA标准B设计
- 服务系数: 1.15
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证

Features:

- HP: 1/3HP-3HP
- Pole: 2P
- Frame: 56J
- Rolled Steel
- NEMA design: B
- Service Factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56J	F56J 1/3M2A	230/460	60	TEFC	1.15	1.7/0.85	22.5
	3600	56J	F56J 1/3M2D	575	60	TEFC	1.15	0.68	22.5
1/2	3600	56J	F56J 1/2M2A	230/460	60	TEFC	1.15	2.0/1.0	24.5
	3600	56J	F56J 1/2M2D	575	60	TEFC	1.15	0.80	24.5
3/4	3600	56J	F56J 3/4M2A	230/460	60	TEFC	1.15	2.6/1.3	25
	3600	56J	F56J 3/4M2D	575	60	TEFC	1.15	1.05	25
1	3600	56J	F56J 1M2A	230/460	60	TEFC	1.15	3.4/1.7	25.5
	3600	56J	F56J 1M2D	575	60	TEFC	1.15	1.36	25.5
1.5	3600	56J	F56J 1.5M2A	230/460	60	TEFC	1.15	4.4/2.2	31
	3600	56J	F56J 1.5M2D	575	60	TEFC	1.15	1.76	31
2	3600	56J	F56J 2M2A	230/460	60	TEFC	1.15	5.1/2.85	35
	3600	56J	F56J 2M2D	575	60	TEFC	1.15	2.28	35
3	3600	56J	F56J 3M2A	230/460	60	TEFC	1.15	7.8/3.9	40
	3600	56J	F56J 3M2D	575	60	TEFC	1.15	3.12	40