

## 弹性底座电机

# Resilient Base Motor

### 性能特点:

- 功率: 1/4HP-2HP
- 极数: 4P
- 电容运行
- 机座: 48、56
- 卷钢板壳
- NEMA标准N设计
- 服务系数: 1.0, 1.15, 1.25, 1.35
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证
- 可接受手动或自动保护器

### Features:

- HP: 1/4HP-2HP
- Pole: 4P
- Capacitor Run
- Frame: 48、56
- Rolled Steel
- NEMA design N
- Service Factor: 1.0, 1.15, 1.25, 1.35
- Insulation Class: F (UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified
- Accept Manual or Auto Thermal Protector



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	BRGS.	S.F	Full Load AMPS	WGT. LBS.
1/4	1800	48	D48 1/4S4C-Y	115/230	60	ODP	SLEEVE	1.0	2.7/1.4	14
	1800	48	D48 1/4S4C-Y	115/230	60	ODP	BALL	1.35	2.8/1.4	14
1/3	1800	48	D48 1/3S4C-Y	115/208-230	60	ODP	SLEEVE	1.35	3.9/2.15-1.95	16
	1800	56	D56 1/3S4C-Y	115/230	60	ODP	BALL	1.35	3.6/1.8	18
1/2	1800	48	D48 1/2S4C-Y	115/230	60	ODP	SLEEVE	1.0	4.7/2.45	19
	1800	56	D56 1/2S4C-Y	115/230	60	ODP	BALL	1.25	4.6/2.3	20
3/4	1800	56	D56 3/4S4C-Y	115/230	60	ODP	BALL	1.15	7.5/3.9	23
1	1800	56	D56 1S4C-Y	115/230	60	ODP	BALL	1.15	9.5/4.7	38
1.5	1800	56	D56 1.5S4C-Y	115/230	60	ODP	BALL	1.15	14.2/7.2	45
2	1800	56	D56 2S4C-Y	115/230	60	ODP	BALL	1.15	17.2/8.7	47