

封闭式单相空压机电机

Totally Enclosed Single-Phase Air-Compressor Motor

性能特点:

- 功率: 1-10HP
- 极数: 2P, 4P
- 机座: 56-215T
- 起动转矩: $T_{st} \geq 250\%$
- 防护形式: 封闭式
- 防护等级: IP44
- 服务系数: 1.0, 1.15
- 均通过CSA&CUS安全认证
- 可接受手动保护器

Features:

- HP: 1-10HP
- Pole: 2P, 4P
- Frame: 56-215T
- Start Torque: $T_{st} \geq 250\%$
- Enclosure: TEFC
- IP Class: IP44
- Service factor: 1.0, 1.15
- CSA&CUS certified
- Accept Manual Thermal Protector



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	3600	56	F56 1S2C	115/208-230	60	TEFC	1.15	9.44/5.06-4.9	30
	1800	56	F56 1S4C	115/208-230	60	TEFC	1.15	9.7/4.89-5.04	38
	1800	143T	F143T1S4C	115/208-230	60	TEFC	1.15	9.3/5.18-4.78	41
1.5	3600	56	F56 1.5S2C	115/208-230	60	TEFC	1.15	13.14/7.33-6.77	37
	1800	56	F56 1.5S4C	115/208-230	60	TEFC	1.15	13.63/7.09-6.66	42
	1800	145T	F145T1.5S4C	115/208-230	60	TEFC	1.15	13.3/7.1-6.6	45
	3600	145T	F145T1.5S2C	115/208-230	60	TEFC	1.15	13.1/7.0-6.6	41
2	3600	56	F56 2S2C	115/208-230	60	TEFC	1.15	15.3/8.48-7.8	44
	1800	56	F56 2S4C	115/208-230	60	TEFC	1.15	16.51/9.08-8.27	47
	1800	145T	F145T2S4C	115/208-230	60	TEFC	1.15	16.51/9.08-8.27	50
	3600	145T	F145T2S2C	115/208-230	60	TEFC	1.15	16.5/9.2-8.4	48
3	3600	56	F56 3S2C	115/208-230	60	TEFC	1.15	24.0/13-12.3	60
	3600	145T	F145T3S2C	115/208-230	60	TEFC	1.15	24.0/13-12.3	67
	1800	182T	F182T3S4A	208-230/460	60	TEFC	1.15	14.5-12.55/6.35	88
5	3600	184T	F184T5S2A	208-230/460	60	TEFC	1.15	22.95-19.75/10	95
	1800	184T	F184T5S4A	208-230/460	60	TEFC	1.15	23.4-20.3/10.3	96
7.5	1800	213T	F213T7.5S4A	208-230/460	60	TEFC	1.15	33.8-29.5/14.86	153
10	1800	215T	F215T10S4A	208-230/460	60	TEFC	1.0	43-37.8/18.9	190