

封闭式单相电容启动电机

Totally Enclosed Single-Phase Capacitor Start Motor

性能特点:

- 功率: 1/3HP-2HP
- 极数: 2P, 4P
- 电容启动
- 机座: 56、140T
- 卷钢板壳
- NEMA标准N设计
- 服务系数: 1.15
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证
- 可接受手动或自动保护器

Features:

- HP: 1/3HP-2HP
- Pole: 2P, 4P
- Capacitor Start
- Frame: 56、140T
- Rolled steel
- NEMA design: N
- Service factor: 1.15
- Insulation Class: F(UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified
- Accept Manual or Auto Thermal Protector.



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	F561/3S2C-C	115/208-230	60	TEFC	1.15	6.0/2.8-3.0	26
	1800	56	F56 1/3S4C-C	115/208-230	60	TEFC	1.15	5.7/2.7-2.8	27
1/2	3600	56	F561/2S2C-C	115/208-230	60	TEFC	1.15	7.7/3.8-3.9	26
	1800	56	F56 1/2S4C-C	115/208-230	60	TEFC	1.15	7.9/3.8-4.0	28
3/4	3600	56	F56 3/4S2C-C	115/208-230	60	TEFC	1.15	9.8/4.9-4.8	30
	1800	56	F563/4S4C-C	115/208-230	60	TEFC	1.15	10.3/5.3-5.2	32
1	3600	56	F561S2C-C	115/208-230	60	TEFC	1.15	11.8/6.1-5.9	31
	3600	143T	F143T1S2C-C	115/208-230	60	TEFC	1.15	11.8/6.1-5.9	32
	3600	143T	F143T1S2A-C	208-230/460	60	TEFC	1.15	6.2-5.6/2.8	31
	1800	56	F56 1S4C-C	115/208-230	60	TEFC	1.15	13/6.6-6	44
	1800	143T	F143T1S4C-C	115/208-230	60	TEFC	1.15	13/6.6-6.5	45
	1800	143T	F143T1S4A-C	208-230/460	60	TEFC	1.15	6.7-6.0/3.1	44
1.5	3600	56	F56 1.5S2C-C	115/208-230	60	TEFC	1.15	15.3/8.4-7.7	33
	3600	145T	F145T1.5S2C-C	115/208-230	60	TEFC	1.15	15.3/8.4-7.7	34
	3600	145T	F145T1.5S2A-C	208-230/460	60	TEFC	1.15	8.0-7.2/3.6	33
	1800	56	F56 1.5S4C-C	115/208-230	60	TEFC	1.15	17.8/9.3-8.9	49
	1800	145T	F145T1.5S4C-C	115/208-230	60	TEFC	1.15	15.3/8.4-7.7	50
	1800	145T	F145T1.5S4A-C	208-230/460	60	TEFC	1.15	8.7-7.9/4.0	49
2	3600	56	F56 2S2C-C	115/208-230	60	TEFC	1.15	18.6/11-9.9	48
	3600	145T	F145T2S2C-C	115/208-230	60	TEFC	1.15	18.6/11-9.9	49
	3600	145T	F145T2S2A-C	208-230/460	60	TEFC	1.15	10.5-9.3/4.6	48
	1800	56	F56 2S4C-C	115/208-230	60	TEFC	1.15	21.7/11.5-10.8	51
	1800	145T	F145T2S4C-C	115/208-230	60	TEFC	1.15	21/11.3-10.8	52
	1800	145T	F145T2S4A-C	208-230/460	60	TEFC	1.15	11.4-10.3/5.2	51