

单相开启式,一般用途双值电容电机

Single-Phase, Dripproof, General Purpose, Capacitor Start & Run Motor

性能特点:

- 功率: 1/3-10HP
- 极数: 2P, 4P
- 机座: 56-215T
- 防护形式: 开启式
- 防护等级: IP23
- 服务系数: 1.15
- 电容启动和电容运行
- 可接受互换C法兰
- 可接受手动或自动保护器
- 均通过CSA & CUS安全认证

Features:

- HP: 1/3-10HP
- Pole: 2P, 4P
- Frame: 56-215T
- Enclosure: ODP
- IP Class: IP23
- Service Factor: 1.15
- Capacitor Start and Capacitor Run
- Accept C-face Kit
- Accept Manual or Auto Thermal Protector
- CSA&CUS certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	D56 1/3S2C	115/208-230	60	ODP	1.15	4.4/2.25-2.35	23
	1800	56	D56 1/3S4C	115/208-230	60	ODP	1.15	4.3/2.3-2.1	24.5
1/2	3600	56	D56 1/2S2C	115/208-230	60	ODP	1.15	6.0/3.06-3.11	24
	1800	56	D56 1/2S4C	115/208-230	60	ODP	1.15	5.8/3.0-2.8	25
3/4	3600	56	D56 3/4S2C	115/208-230	60	ODP	1.15	8.1/4.2-4.1	26
	1800	56	D56 3/4S4C	115/208-230	60	ODP	1.15	8.27/4-4.22	29
1	3600	56	D56 1S2C	115/208-230	60	ODP	1.15	9.66/5.37-5.24	30
	1800	56	D56 1S4C	115/208-230	60	ODP	1.15	9.5/4.73-4.87	38
	1800	143T	D143T1S4C	115/208-230	60	ODP	1.15	11.5/6.0-5.7	41
1.5	3600	56	D56 1.5S2C	115/208-230	60	ODP	1.15	13/6.98-6.58	37
	1800	56	D56 1.5S4C	115/208-230	60	ODP	1.15	14.2/7.37-7.23	42
	1800	145T	D145T1.5S4C	115/208-230	60	ODP	1.15	15/8.1-7.6	45
2	3600	145T	D145T1.5S2C	115/208-230	60	ODP	1.15	14.5/8.0-7.6	41
	3600	56	D56 2S2C	115/208-230	60	ODP	1.15	17.24/8.55-7.96	44
	1800	56	D56 2S4C	115/208-230	60	ODP	1.15	18.9/9.96	47
	1800	145T	D145T2S4C	115/208-230	60	ODP	1.15	19.0/10-9.3	50
3	3600	145T	D145T2S2C	115/208-230	60	ODP	1.15	18/10.2-9.4	48
	3600	56	D56 3S2C	115/208-230	60	ODP	1.15	12.59-11.28/5.97	60
	3600	145T	D145T3S2C	115/208-230	60	ODP	1.15	25/14.2-13	67
	1800	182T	D182T3S4C	208-230	60	ODP	1.15	13.5-12/6.2	88
5	3600	184T	D184T5S2C	208-230	60	ODP	1.15	22-20/10	95
	1800	184T	D184T5S4C	208-230	60	ODP	1.15	22.5-20/10	96
7.5	1800	213T	D213T7.5S4C	208-230	60	ODP	1.15	32.8-30/15.2	153
10	1800	215T	D215T10S4C	208-230	60	ODP	1.15	41.2-39/19.5	190