

开启式单相电容运行电机

Dripproof Single-Phase Capacitor Run Motor

性能特点:

- 功率: 1/3HP-3HP
- 极数: 2P, 4P
- 电容运行
- 机座: 56、140T
- 卷钢板壳, 互换C法兰
- NEMA标准N设计
- 服务系数: 1.15
- 绝缘等级: F(绝缘结构通过了UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证
- 可接受自动保护器

Features:

- HP: 1/3HP-3HP
- Pole: 2P, 4P
- Capacitor Run
- Frame: 56, 140T
- Rolled steel, C-Face Kit
- NEMA design: N
- Service factor: 1.15
- Insulation Class: F(UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified
- Accept Auto Thermal Protector



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	D56 1/3S2C-Y	115/208-230	60	ODP	1.15	4.7/2.2-2.5	17
	1800	56	D56 1/3S4C-Y	115/208-230	60	ODP	1.15	4.3/2.1-2.3	17
1/2	3600	56	D56 1/2S2C-Y	115/208-230	60	ODP	1.15	5.9/2.9-3.1	18
	1800	56	D56 1/2S4C-Y	115/208-230	60	ODP	1.15	5.8/2.8-3.0	20
3/4	3600	56	D56 3/4S2C-Y	115/208-230	60	ODP	1.15	8.1/4.2-4.1	22
	1800	56	D56 3/4S4C-Y	115/208-230	60	ODP	1.15	8.1/4.0-4.2	25
1	3600	56	D56 1S2C-Y	115/208-230	60	ODP	1.15	12/6.4-5.8	24
	3600	143T	D143T1S2C-Y	115/208-230	60	ODP	1.15	11.5/6.4-5.8	25
	3600	143T	D143T1S2A-Y	208-230/460	60	ODP	1.15	5.8-5.4/2.6	24
	1800	56	D56 1S4C-Y	115/208-230	60	ODP	1.15	11.5/6.0-5.7	36
	1800	143T	D143T1S4C-Y	115/208-230	60	ODP	1.15	11.5/6.0-5.7	37
	1800	143T	D143T1S4A-Y	208-230/460	60	ODP	1.15	4.8-5.3/2.7	36
1.5	3600	56	D56 1.5S2C-Y	115/208-230	60	ODP	1.15	14.5/7.8-7.2	34
	3600	145T	D145T1.5S2C-Y	115/208-230	60	ODP	1.15	14.5/8.0-7.6	32
	3600	145T	D145T1.5S2A-Y	208-230/460	60	ODP	1.15	7.5-7.0/3.4	31
	1800	56	D56 1.5S4C-Y	115/208-230	60	ODP	1.15	15.5/8.1-7.6	42
	1800	145T	D145T1.5S4C-Y	115/208-230	60	ODP	1.15	15.5/8.1-7.6	43
	1800	145T	D145T1.5S4A-Y	208-230/460	60	ODP	1.15	7.1-6.7/3.4	42
2	3600	56	D56 2S2C-Y	115/208-230	60	ODP	1.15	18/10.1-9.2	41
	3600	145T	D145T2S2C-Y	115/208-230	60	ODP	1.15	18/10.2-9.4	42
	3600	145T	D145T2S2A-Y	208-230/460	60	ODP	1.15	9.8-9.1/4.5	41
	1800	56	D56 2S4C-Y	115/208-230	60	ODP	1.15	19.0/10-9.3	42
	1800	145T	D145T2S4C-Y	115/208-230	60	ODP	1.15	19.0/10-9.3	43
	1800	145T	D145T2S4A-Y	208-230/460	60	ODP	1.15	9.8-9.1/4.5	42
3	3600	56	D56 3S2C-Y	115/208-230	60	ODP	1.15	25/14.2-13	49
	3600	145T	D145T3S2C-Y	115/208-230	60	ODP	1.15	25/14.2-13	50
	3600	145T	D145T3S2A-Y	208-230/460	60	ODP	1.15	14-12.5/6.5	49