

开启式单相电容启动电机

Dripproof Single-Phase Capacitor Start Motor

性能特点:

- 功率: 1/3HP-2HP
- 极数: 2P, 4P
- 电容启动
- 机座: 56、140T
- 卷钢板壳
- NEMA标准N设计
- NEMA服务系数: 1.15
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证

Features:

- HP: 1/3HP-2HP
- Pole: 2P, 4P
- Capacitor Start
- Frame: 56、140T
- Rolled steel
- NEMA design: N
- Service factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified



| HP | RPM | NEMA FRAME | Model | Volts | HZ | ENCL. | S.F | Full Load AMPS | WGT. LBS. |
|-----|------|------------|---------------|---------|----|-------|------|----------------|-----------|
| 1/3 | 3600 | 56 | D561/3S2C-C | 115/230 | 60 | ODP | 1.15 | 7.0/3.5 | 23 |
| | 1800 | 56 | D56 1/3S4C-C | 115/230 | 60 | ODP | 1.15 | 7.4/3.7 | 24 |
| 1/2 | 3600 | 56 | D561/2S2C-C | 115/230 | 60 | ODP | 1.15 | 8.6/4.3 | 24 |
| | 1800 | 56 | D56 1/2S4C-C | 115/230 | 60 | ODP | 1.15 | 7.9/4.0 | 25 |
| 3/4 | 3600 | 56 | D56 3/4S2C-C | 115/230 | 60 | ODP | 1.15 | 11.4/5.7 | 27 |
| | 1800 | 56 | D563/4S4C-C | 115/230 | 60 | ODP | 1.15 | 10.2/5.1 | 30 |
| 1 | 3600 | 56 | D561S2C-C | 115/230 | 60 | ODP | 1.15 | 13.2/6.6 | 29 |
| | 3600 | 143T | D143T1S2C-C | 115/230 | 60 | ODP | 1.15 | 11.8/5.9 | 30 |
| | 3600 | 143T | D143T1S2A-C | 230/460 | 60 | ODP | 1.15 | 6.3/2.4 | 29 |
| | 1800 | 56 | D56 1S4C-C | 115/230 | 60 | ODP | 1.15 | 13/6.6 | 42 |
| | 1800 | 143T | D143T1S4C-C | 115/230 | 60 | ODP | 1.15 | 13/6.7 | 43 |
| | 1800 | 143T | D143T1S4A-C | 230/460 | 60 | ODP | 1.15 | 7.1/3.3 | 42 |
| 1.5 | 3600 | 56 | D56 1.5S2C-C | 115/230 | 60 | ODP | 1.15 | 17.6/8.8 | 32 |
| | 3600 | 145T | D145T1.5S2C-C | 115/230 | 60 | ODP | 1.15 | 15.3/7.7 | 23 |
| | 3600 | 145T | D145T1.5S2A-C | 230/460 | 60 | ODP | 1.15 | 8.1/3.3 | 32 |
| | 1800 | 56 | D56 1.5S4C-C | 115/230 | 60 | ODP | 1.15 | 17.8/8.8 | 47 |
| | 1800 | 145T | D145T1.5S4C-C | 115/230 | 60 | ODP | 1.15 | 16.2/8.2 | 48 |
| | 1800 | 145T | D145T1.5S4A-C | 230/460 | 60 | ODP | 1.15 | 9.1/4.2 | 47 |
| 2 | 3600 | 56 | D56 2S2C-C | 115/230 | 60 | ODP | 1.15 | 23/11.5 | 46 |
| | 3600 | 145T | D145T2S2C-C | 115/230 | 60 | ODP | 1.15 | 18.6/9.9 | 47 |
| | 3600 | 145T | D145T2S2A-C | 230/460 | 60 | ODP | 1.15 | 10.5/4.1 | 46 |
| | 1800 | 56 | D56 2S4C-C | 115/230 | 60 | ODP | 1.15 | 23.4/11.7 | 49 |
| | 1800 | 145T | D145T2S4C-C | 115/230 | 60 | ODP | 1.15 | 16.8/8.3 | 50 |
| | 1800 | 145T | D145T2S4A-C | 230/460 | 60 | ODP | 1.15 | 11.4/5.5 | 49 |