

TEAO 48、56风扇电机

TEAO 48、56 Fan Motor

性能特点:

- 功率: 1/10HP-1.5HP
- 极数: 4P, 6P, 8P
- 机座号: 48、56
- 卷钢板壳
- NEMA标准N设计
- NEMA服务系数: 1.0, 1.4
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: TEAO
- 防护等级: IP44, IP55
- 带自动热保护器
- 电机均通过CSA&CUS安全认证

Features:

- HP: 1/10HP-1.5HP
- Pole: 4P, 6P, 8P
- Frame: 48、56
- Rolled steel
- NEMA design: N
- NEMA service factor: 1.0, 1.4
- Insulation Class: F(UL approved)
- Enclosure: TEAO
- IP Class: IP44, IP55
- Accept Auto Thermal Protector
- CSA&CUS certified



HP	RPM	NEMA FRAME	PH	Model	Volts	HZ	ENCL.	OVER LOAD	S.F	Full Load AMPS	WGT. LBS.
1/10	1625	48	1	A48 1/10S4C	115/230	60	TEAO	AUTO	1.0	1.3/0.65	12
1/8	1625	48	1	A48 1/8S4C	115/230	60	TEAO	AUTO	1.0	1.64/0.84	12
	1080	48	1	A48 1/8S6C	115/230	60	TEAO	AUTO	1.0	1.6/0.8	13
	810	48	1	A48 1/8S8C	115/230	60	TEAO	AUTO	1.0	2.1/1.05	14
1/6	1625	48	1	A48 1/6S4C	115/230	60	TEAO	AUTO	1.0	2.17/1.09	12
	1080	48	1	A48 1/6S6C	115/230	60	TEAO	AUTO	1.0	2.12/1.06	13
	810	48	1	A48 1/6S8C	115/230	60	TEAO	AUTO	1.0	2.75/1.38	14
1/5	1625	48	1	A48 1/5S4C	115/230	60	TEAO	AUTO	1.0	2.2/1.1	12
	1080	48	1	A48 1/5S6C	115/230	60	TEAO	AUTO	1.0	2.6/1.3	13
	810	48	1	A48 1/5S8C	115/230	60	TEAO	AUTO	1.0	2.8/1.4	16
1/4	1625	48	1	A48 1/4S4C	115/230	60	TEAO	AUTO	1.0	2.7/1.4	12
	1080	48	1	A48 1/4S6C	115/230	60	TEAO	AUTO	1.0	3.0/1.5	14
	810	48	1	A48 1/4S8C	115/230	60	TEAO	AUTO	1.0	3.6/1.8	16
1/3	1625	48	1	A48 1/3S4C	115/230	60	TEAO	AUTO	1.0	4.1/2.06	17
	1080	48	1	A48 1/3S6C	115/230	60	TEAO	AUTO	1.0	3.6/1.8	13
	810	48	1	A48 1/3S8C	115/230	60	TEAO	AUTO	1.0	4.2/2.1	18
1/2	1625	48	1	A48 1/2S4C	115/230	60	TEAO	AUTO	1.0	4.9/2.45	20
	1080	48	1	A48 1/2S6C	115/230	60	TEAO	AUTO	1.0	5.1/2.55	21
	810	48	1	A48 1/2S8C	115/230	60	TEAO	AUTO	1.0	7.1/3.7	22
3/4	1625	48	1	A48 3/4S4C	115/230	60	TEAO	AUTO	1.0	6.7/3.5	21
	1080	48	1	A48 3/4S6C	115/230	60	TEAO	AUTO	1.0	7.8/3.9	23
	810	48	1	A48 3/4S8C	115/230	60	TEAO	AUTO	1.0	8.7/4.4	26
	810	56	1	A563/4S8C	115/208-230	60	TEAO	AUTO	1.0	8.1/4.8-4.3	33
1	1625	48	1	A48 1S4C	115/230	60	TEAO	AUTO	1.0	9.5/4.95	22
	1080	48	1	A48 1S6C	115/230	60	TEAO	AUTO	1.0	11.0/5.5	27
	810	48	1	A48 1S8C	115/230	60	TEAO	AUTO	1.0	11.5/6.04	30
	810	56	1	A561S8C	115/208-230	60	TEAO	AUTO	1.0	5.04/2.8-2.5	35
	1750	56	1	A561S4C	115/208-230	60	TEAO	AUTO	1.4	8.7/4.8-4.5	38
	1750	56	3	A561M4A	208-230/460	60	TEAO	AUTO	1.4	4.0-3.6/1.8	26
	810	56	3	A561M8A	208-230/460	60	TEAO	AUTO	1.0	5.6-6.6/3.4	35
1.5	1750	56	1	A561.5S4C	115/208-230	60	TEAO	AUTO	1.4	13.4/7.3-6.8	42
	1750	56	3	A561.5M4A	208-230/460	60	TEAO	AUTO	1.4	6.5-5.9/2.95	37