

液压泵电机

Hydraulic Pump Motor

性能特点:

- 功率: 1HP-3HP
- 极数: 2P, 4P
- 机座: 56C, 56HC
- 卷钢板壳
- NEMA标准B设计
- 服务系数: 1.15
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 封闭式
- 防护等级: IP44
- 均通过CSA&CUS安全认证

Features:

- HP: 1HP-3HP
- Pole: 2P, 4P
- Frame: 56C, 56HC
- Rolled steel
- NEMA design: B
- Service factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: TEFC
- IP Class: IP44
- CSA&CUS certified



HP	RPM	NEMA FRAME	Model	Volts	HZ	PH	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	1800	56C	F56C1S4C	115/230	60	1	TEFC	1.15	9.2/5.0-4.7	38
	3600	56C	F56C1S2C	115/230	60	1	TEFC	1.15	8.3/4.4	30
2	1800	56C	F56C2S4C	115/230	60	1	TEFC	1.15	16.5/8.3	47
	3600	56C	F56C2S2C	115/230	60	1	TEFC	1.15	16.5/8.4	44
3	3600	56HC	F56HC3S2C	230	60	1	TEFC	1.15	13.0	60
1	1800	56C	F56C1M4A	230/460	60	3	TEFC	1.15	3.4/1.7	33
	1800	56C	F56C1M4D	575	60	3	TEFC	1.15	1.4	33
1.5	1800	56C	F561.5M4A	230/460	60	3	TEFC	1.15	5.2/2.6	37
	1800	56C	F56C1.5M4D	575	60	3	TEFC	1.15	2.0	37
2	1800	56C	F56C2M4A	230/460	60	3	TEFC	1.15	6.0/3.0	40
	1800	56C	F56C2M4D	575	60	3	TEFC	1.15	2.5	40
	3600	56C	F56C2M2D	575	60	3	TEFC	1.15	2.1	34
3	1800	56HC	F56HC3M4A	230/460	60	3	TEFC	1.15	9.0/4.5	47
	1800	56HC	F56HC3M4D	575	60	3	TEFC	1.15	3.6	47