

56机座开启式单相喷射泵电机

56 Frame Dripproof Single-Phase Jet Pump Motor

性能特点:

- 功率: 1/3HP-3HP
- 电容启动
- 机座: 56J
- 卷钢板壳
- NEMA标准N设计
- 服务系数: 1.15
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证

Features:

- HP: 1/3HP-3HP
- Capacitor Start
- Frame: 56J
- Rolled Steel
- NEMA design: N
- Service Factor: 1.15
- Insulation Class: F(UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56J	D56J 1/3S2C-C	115/230	60	ODP	1.15	6.4/3.5	25
1/2	3600	56J	D56J 1/2S2C-C	115/230	60	ODP	1.15	7.9/4	26
3/4	3600	56J	D56J 3/4S2C-C	115/230	60	ODP	1.15	9.6/4.8	28
1	3600	56J	D56J 1S2C-C	115/230	60	ODP	1.15	11.4/5.8	30
1.5	3600	56J	D56J 1.5S2C-C	115/230	60	ODP	1.15	15.7/7.8	33
2	3600	56J	D56J 2S2C-C	115/230	60	ODP	1.15	20.8/10.4	47
3	3600	56J	D56J 3S2C-C	115/230	60	ODP	1.15	28.5/14.3	57