

单相游泳池泵电机

Single-Phase Pool and Spa Pump Motor

性能特点:

- 功率: 1/3HP-2HP
- 极数: 2P
- 机座: 56J
- 电容运行
- 卷钢板壳
- NEMA标准N设计
- 服务系数: 1.1-1.67
- 绝缘等级: F (绝缘结构通过了UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA&CUS安全认证

Features:

- HP: 1/3HP-2HP
- Pole: 2P
- Frame: 56J
- Capacitor Run
- Rolled Steel
- NEMA design: N
- Service Factor: 1.1-1.67
- Insulation Class: F (UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
3/4	3600	56J	D56J3/4S2C-Y-1.67	115/230	60	ODP	1.67	8.6/4.3	24
1	3600	56J	D56J1S2C-Y-1.4	115/230	60	ODP	1.4	10.24/5.51	28
	3600	56J	D56J1S2C-Y-1.65	115/230	60	ODP	1.65	9.65/5	28
1.5	3600	56J	D56J1.5S2C-Y-1.3	115/230	60	ODP	1.3	12.53/6.31	35
2	3600	56J	D56J2S2C-Y-1.1	115/230	60	ODP	1.1	12.53/6.31	43
	3600	56J	D56J2S2C-Y-1.2	115/230	60	ODP	1.2	17.6/8.8	43
	3600	56J	D56J2S2C-Y-1.3	115/230	60	ODP	1.3	17.4/8.7	43