

电阻启动电机

Resistance Start Motor

性能特点:

- 功率: 1/4HP-3/4HP
- 极数: 4P
- 机座号: 48、56
- 卷钢板壳
- 电阻启动
- NEMA标准N设计
- NEMA服务系数: 1.0, 1.15, 1.35
- 绝缘等级: F极 (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23

Features:

- HP: 1/4HP-3/4HP
- Pole: 4P
- Frame: 48、56
- Rolled steel
- Resistance Start
- NEMA design: N
- NEMA service factor: 1.0, 1.15, 1.35
- Insulation Class: F(UL approved)
- Enclosure: ODP
- IP Class: IP23



HP	RPM	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/4	1800	48	D481/4S4C-U	115	60	ODP	1.0	4.16	12
	1800	48	D481/4S4C-U-1	115	60	ODP	1.35	4.16	12
	1800	56C	D56C1/4S4A-U	208-230	50	ODP	1.15	2.08-2.16	22
1/3	1800	48	D481/3S4C-U	115	60	ODP	1.0	5.11	13
1/2	1800	48	D481/2S4C-U	115	60	ODP	1.0	6.96	14
3/4	1800	48	D483/4S4C-U	115	60	ODP	1.0	9.38	16