

单相封闭式,一般用途双值电容电机

Single-Phase, Totally Enclosed, General Purpose, Capacitor Start & Run Motor

性能特点:

- 功率: 1/3-10HP
- 极数: 2P, 4P
- 机座: 56-215T
- 防护形式: 封闭式
- 防护等级为: IP44
- 服务系数: 1.15
- 电容启动和电容运行
- 可接受互换C法兰
- 可接受手动或自动保护器
- 均通过CSA & CUS安全认证

Features:

- HP: 1/3-10HP
- Pole: 2P, 4P
- Frame: 56-215T
- Enclosure: TEFC
- IP Class: IP44
- Service Factor: 1.15
- Capacitor Start and Capacitor Run
- Accept C-face Kit
- Accept Manual or Auto Thermal Protector
- CSA&CUS certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	3600	56	F56 1/3S2C	115/208-230	60	TEFC	1.15	4.55/2.19-2.36	23
	1800	56	F56 1/3S4C	115/208-230	60	TEFC	1.15	4.99/2.31-2.58	23
1/2	3600	56	F56 1/2S2C	115/208-230	60	TEFC	1.15	6.01/3.06-3.11	24
	1800	56	F56 1/2S4C	115/208-230	60	TEFC	1.15	6.68/3.11-3.45	25
3/4	3600	56	F56 3/4S2C	115/208-230	60	TEFC	1.15	8.47/4.18-4.29	26
	1800	56	F56 3/4S4C	115/208-230	60	TEFC	1.15	8.27/4-4.22	29
1	3600	56	F56 1S2C	115/208-230	60	TEFC	1.15	9.44/5.06-4.9	30
	1800	56	F56 1S4C	115/208-230	60	TEFC	1.15	9.7/4.89-5.04	38
	1800	143T	F143T1S4C	115/208-230	60	TEFC	1.15	9.3/5.18-4.78	40
1.5	3600	56	F56 1.5S2C	115/208-230	60	TEFC	1.15	13.14/7.33-6.77	38
	1800	56	F56 1.5S4C	115/208-230	60	TEFC	1.15	13.63/7.09-6.66	43.8
	1800	145T	F145T1.5S4C	115/208-230	60	TEFC	1.15	13.3/7.1-6.6	45
2	3600	145T	F145T1.5S2C	115/208-230	60	TEFC	1.15	13.1/7.0-6.6	40
	3600	56	F56 2S2C	115/208-230	60	TEFC	1.15	15.3/8.48-7.8	44
	1800	56	F56 2S4C	115/208-230	60	TEFC	1.15	16.51/9.08-8.27	47
	1800	145T	F145T2S4C	115/208-230	60	TEFC	1.15	16.51/9.08-8.27	55
3	3600	145T	F145T2S2C	115/208-230	60	TEFC	1.15	16.5/9.2-8.4	50
	3600	56	F56 3S2C	115/208-230	60	TEFC	1.15	24.0/13-12.3	62
	3600	145T	F145T3S2C	115/208-230	60	TEFC	1.15	24.0/13-12.3	67
	1800	182T	F182T3S4A	208-230/460	60	TEFC	1.15	14.5-12.55/6.35	91.5
5	3600	184T	F184T5S2A	208-230/460	60	TEFC	1.15	22.95-19.75/10	95
	1800	184T	F184T5S4A	208-230/460	60	TEFC	1.15	23.4-20.3/10.3	110
7.5	1800	213T	F213T7.5S4A	208-230/460	60	TEFC	1.15	33.8-29.5/14.86	153
10	1800	215T	F215T10S4A	208-230/460	60	TEFC	1.15	43-37.8/18.9	190