

三相开启式高效电机

Three-Phase Drip-Proof High-Efficiency Motor

性能特点:

- 功率: 1HP-20HP
- 极数: 2P, 4P, 6P
- 机座: 143T-256T
- 卷钢板壳
- NEMA标准B设计
- 可接受互换C法兰
- 服务系数: 1.15
- 绝缘等级: F (绝缘结构通过UL认证)
- 防护形式: 开启式
- 防护等级: IP23
- 均通过CSA & CUS 安全认证
- 均通过美国EPACT(CC)和加拿大EEV高能效认证

Features:

- HP: 1HP-20HP
- Pole: 2P, 4P, 6P
- Frame: 143T-256T
- Rolled steel
- NEMA design B
- Accept C-face Kit
- Service factor: 1.15
- Insulation Class: F (UL approved)
- Enclosure: ODP
- IP Class: IP23
- CSA&CUS certified
- EPACT(CC) & EEV certified



HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	3600	143T	ED143T1M2A	2208-230/460	60	ODP	1.15	3.7-3.4/1.7	31.5
	3600	143T	ED143T1M2D	575	60	ODP	1.15	1.36	31.5
	1800	143T	ED143T1M4A	208-230/460	60	ODP	1.15	3.5-3.2/1.6	40.5
	1800	143T	ED143T1M4D	575	60	ODP	1.15	1.28	40.5
	1200	145T	ED145T1M6A	208-230/460	60	ODP	1.15	4.2-3.8/1.9	40
	1200	145T	ED145T1M6D	575	60	ODP	1.15	1.52	40
1.5	3600	143T	ED143T1.5M2A	208-230/460	60	ODP	1.15	4.6-4.2/2.1	37
	3600	143T	ED143T1.5M2D	575	60	ODP	1.15	1.68	37
	1800	145T	ED145T1.5M4A	208-230/460	60	ODP	1.15	5.1-4.6/2.3	44
	1800	145T	ED145T1.5M4D	575	60	ODP	1.15	1.84	44
	1200	182T	ED182T1.5M6A	208-230/460	60	ODP	1.15	5.6-5.0/2.5	66.5
	1200	182T	ED182T1.5M6D	575	60	ODP	1.15	2.0	66.5
2	3600	145T	ED145T2M2A	208-230/460	60	ODP	1.15	5.9-5.4/2.7	37.5
	3600	145T	ED145T2M2D	575	60	ODP	1.15	2.16	37.5
	1800	145T	ED145T2M4A	208-230/460	60	ODP	1.15	6.8-6.2/3.1	47.5
	1800	145T	ED145T2M4D	575	60	ODP	1.15	2.48	47.5
	1200	184T	ED184T2M6A	208-230/460	60	ODP	1.15	6.8-6.2/3.1	73
	1200	184T	ED184T2M6D	575	60	ODP	1.15	2.5	73
3	3600	145T	ED145T3M2A	208-230/460	60	ODP	1.15	8.8-8.0/4.0	41
	3600	145T	ED145T3M2D	575	60	ODP	1.15	3.2	41
	1800	182T	ED182T3M4A	208-230/460	60	ODP	1.15	8.8-8.0/4.0	78
	1800	182T	ED182T3M4G	220/380	60	ODP	1.15	8.5/4.5	78
	1800	182T	ED182T3M4D	575	60	ODP	1.15	3.2	78
	1200	213T	ED213T3M6A	208-230/460	60	ODP	1.15	9.5-8.6/4.3	103
	1200	213T	ED213T3M6D	575	60	ODP	1.15	3.5	103
5	3600	182T	ED182T5M2A	208-230/460	60	ODP	1.15	14.1-12.8/6.4	73
	3600	182T	ED182T5M2D	575	60	ODP	1.15	5.12	73
	1800	184T	ED184T5M4A	208-230/460	60	ODP	1.15	14.3-13.0/6.5	85
	1800	184T	ED184T5M4G	220/380	60	ODP	1.15	13.5/7.3	85
	1800	184T	ED184T5M4D	575	60	ODP	1.15	5.2	85
	1200	215T	ED215T5M6A	208-230/460	60	ODP	1.15	15.6-14.2/7.1	112
	1200	215T	ED215T5M6D	575	60	ODP	1.15	5.7	112
7.5	3600	184T	ED184T7.5M2A	208-230/460	60	ODP	1.15	19.6-17.8/8.9	79.5
	3600	184T	ED184T7.5M2D	575	60	ODP	1.15	7.12	79.5
	1800	213T	ED213T7.5M4A	208-230/460	60	ODP	1.15	20.9-19.0/9.5	120
	1800	213T	ED213T7.5M4G	220/380	60	ODP	1.15	19.8/10.6	120
	1800	213T	ED213T7.5M4D	575	60	ODP	1.15	7.6	120
10	3600	213T	ED213T10M2A	208-230/460	60	ODP	1.15	27.7-25.2/12.6	114
	3600	213T	ED213T10M2D	575	60	ODP	1.15	10.0	114
	1800	215T	ED215T10M4A	208-230/460	60	ODP	1.15	27.5-25.0/12.5	131
	1800	215T	ED215T10M4G	220/380	60	ODP	1.15	26.5/14	131
	1800	215T	ED215T10M4D	575	60	ODP	1.15	10	131
15	3600	215T	ED215T15M2A	208-230/460	60	ODP	1.15	37.8-34.4/17.2	126
	3600	215T	ED215T15M2D	575	60	ODP	1.15	13.8	126
	1800	254T	ED254T15M4A	208-230/460	60	ODP	1.15	41.8-38.0/19.0	198
	1800	254T	ED254T15M4D	575	60	ODP	1.15	15.2	198
20	1800	256T	ED256T20M4A	208-230/460	60	ODP	1.15	56.5-51.4/25.7	210
	1800	256T	ED256T20M4D	575	60	ODP	1.15	20.6	210