欢迎关注中大。亲爱的朋友，与你们结识是我们公司的荣幸，因为这不但使我们与你之间搭建起合作的桥梁，更为你选择产品的同时，创建出物超所值的享受，这不只是承诺，因为真实的行动很久以前已经开始，为了让你对本公司的产品有更全面的了解，今天请你阅读以下篇章。
Our Dear Friends, We feel greatly honoured to make your acquaintance because it will not only set up a cooperative bridge between you and us, but also you could enjoy the great value of the product in your choice. It is not merely a commitment and the real action has been started early. Please read following chapters for an intimate knowledge of our company.

电动机 MOTOR

5	I	K	40	R	G N -	C	T
①	②	③	④	⑤	⑥	⑦	⑧

①	电动机的尺寸 Motor Frame Size	4: 80mm 5: 90mm 6: 104mm
②	机型名称 Motor Type	I: 感应电动机 Induction Motor R: 可逆电动机 Reversible Motor
③	系列名称 Series	K: K系列 K Series
④	输出功率 Output Power (W) (例 e.g.)	40: 40W
⑤	R: 表示带调速电动机；无: 表示未带The Suffix "-R" after the Output Power Means Speed Adjustable Motor.	
⑥	转轴形状 Motor Shaft Type	GN: GN型齿轮轴 GN Type Pinion Shaft GU: GU型齿轮轴 GU Type Pinion Shat
⑦	电源电压·极数Voltage·Poles	A: 单Single-Phase100V 110V 50/60Hz 4P C: 单相Single-Phase220V 230V 50/60Hz 4P E: 单相Single-Phase110V、120V 60Hz 4P H: 单相Single-Phase220V、230V 60Hz 4P S: 三相Three-Phase200/220/230V 50/60Hz 4P S3: 三相Three-Phase380/415V 50/60Hz 4P
⑧	T: 带端子箱型Terminal Box Type F: 带风扇 W/Fan FF: 带强制风扇 W/Forced Fan M: 无励磁动作型电磁制动电动机 Power Off Activated Type Electromagnetic Brake Motor P: 附热保护器 Thermal protector	

注：对于单相电机同一电源代号不同电压所配置的电容器可能有所不同，以铭牌标识为准。
Notes: The capacitor may be different of a sigle phase motor with same power code and different voltage. Please check nameplate first.

减速机REDUCER

5	G N	5 0	RH
①	②	③	④

①	减速机安装尺寸 Gearhead Frame Size	4: 80mm 5: 90mm 6: 104mm
②	类型Gear Type	GN：GN型齿轮GN Type Gear GU：GU型齿轮轴GU Type Gear
③	减速比Gear Ratio 例e.g. 50：减速比 Reduction Ratio：50	
④	输出轴类型 Type of output shaft RH：蜗轮蜗杆空心轴输出 Hollow worm shaft RA：蜗轮蜗杆实心轴输出 Worm output shaft RC：弧锥齿空心轴输出 Spiral bevel hollow shaft RT：弧锥齿实心轴输出 Spiral bevel output shaf	