


Leads: 300mm ± 10, type: UL1015 AWG20.


Motor



Gearbox



Wire diagram



MOTOR DATA		Ratio	i=303
Model of Motor	Z62DP2460-30S	Stage	3
Roted Voltage	24VDC	In. Class	B
Rated power	60W	Protection class	IP20
Rated current	3.6A ± 10%	Direction	Same as motor
Rated speed	3000rpm ± 10%	Ambient Temp.	-10° C ~ +40° C
Rated torque	0.191N.m	Bearing	Ball bearing
No load current	≤ 1.5A	Gearbox structure	Combinated
No load speed	3500rpm ± 10%	Rated torque	42.25N.M
Duty	S2 (30m)	The max torque gearmotor bear continuous	45N.M
Insulation resistance	>20M Ω	Instantaneous max torque	90N.M
Bursh life	2000h	Transimit Efficiency	73%
Electric strength	660V/S	Noise	<60dB (L=100cm)

借(通)用件登记  
旧底图总号

底图总号

签字

日期

						ZD MOTOR		
						Type	Z62DP2460-30S / 62PM303K	
						Drawing		
标记	处数	分区	更改文件号	签名	年月日	阶段标记	重量	比例
设计						S		1:1
校对								
审核								零件代号 ZD-DC20120410001
工艺			批准			共 1 张	第 1 张	存贮号